





PRODUCT DESCRIPTION

Minimalist in design but loud in its statement, oval frames illuminate translucent panels. Available in Natural Aged Brass with Dichroic glass panels or Brushed Gunmetal with Patterned Acrylic Panels, the subtleties in the design become more vivid as they react to light. Most notably in the Dichroic glass panels where its iridescent hues become more vibrant with light and the layering effect adds a colorful element to the design. Intentionally designed with various dimensions, the multiple pendant configurations can be fixed together in polygonal cages held by removable clasps or simply free-float on the thin low voltage cables that suspend each frame.

1.5"= 10" 1.60" Max OAH *max overall height

MEASUREMENTS

DIMENSION : 10" L x 10" W x 39.25" H

MAX OAH : 160" OAH

CANOPY : 7.75" W x 1.5" H x 7.75" L

HANGING WEIGHT : 11.5 lb

LAMPING

INPUT VOLTAGE : 120-277V LUMENS : 4,400 Rated (2,640 Del.)

BULB : 18W LED DC Integrated, 54W Total

BULB INCLUDED : (Integrated)

DIMMABLE : 3-in-1: Triac, ELV, 0-10V

CRI : 90 CRI COLOR_TEMP : 3000K

FINISHES OPTION



Gunmetal (GM)

Natural Aged Brass (NAB)

MATERIAL

Steel, Aluminum, Glass

RATINGS

cETLus Dry Location



ADDITIONAL

SLOPE: 30

RATED LIFE 20000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments