Quantity:



PRODUCT DESCRIPTION

White Acrylic diffusers are miter cut and beveled along the edge of these mirror frames allowing for wider, and brighter lighting. Robust in size, these mirrors feature excellent construction and 2CCT light selection using a discreet touch switch on the frames edge. Hardwire the mirrors to a dimmer switch to control the brightness and the memory function on the LED will recall the chosen color temperature of the previous setting.

> MEASUREMENTS DIMENSION HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED CRI COLOR_TEMP

: 24" W x 36" H x 6.25" Ext : 45.32 lb

: 120-277V : 4,000 Rated (1,500 Del.) : 47W LED DC Integrated , 47W Total : (Integrated) : 90 CRI : 3000K





MATERIAL Aluminum, PC, Glass

RATINGS CETLus Damp Location CA Title 24



ADDITIONAL RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name: Job Type: Quantity: Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.