




PRODUCT DESCRIPTION

An update to our popular Line series, the Line 5CCT uses a wider profile of aluminum with adjustable color temperatures. Simply toggle between the 5 settings: 2700-3000-3500-4000-500K to suit the space where it is installed. Following the original design's premise, the Line is a straight and flat bar that indirectly casts light indirectly on the surface behind it.



MEASUREMENTS DIMENSION BACK PLATE HANGING WEIGHT

LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP LIGHTING_DIRECTION : 96" L 4.5" H x 2.75" Ext : 4.75" W x 11" H x 48" HCO : 6.16 lb

: 120V : 4,200 Rated (3,500 Del.)

: 30W LED AC Integrated , 60W Total : (Integrated)

- : : 90 CRI : 27-30-35-40-50K
 - : Indirect

FINISHES OPTION



MATERIAL Aluminum, PC

RATINGS

cETLus Wet Location CA Title 24 ADA



ADDITIONAL

INSTALL UP/DOWN: Vertical/Horizo SLOPE: RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments