



## **PRODUCT DESCRIPTION**

Inconspicuously recessed within its cylindrical house, an extending arm transforms this surface mounted light fixture into an adjustable spotlight. Simply unthread the top half along the seam to extend the frame length and swing the fixture into position. Twist the lens on the face of this fixture to adjust its beam angle spread. Available in Black and White and two apertures that include a mud-in ring for an even cleaner installation.

MEASUREMENTS DIMENSION CANOPY HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR\_TEMP

: 5.25" L x 5.25" W x 3.25" H : 5.25" W x 0.25" H x 5.25" L : 0.88 lb

: 120-277V : 1,200 Rated (1,030 Del.) : 12W LED DC Integrated , 12W Total : (Integrated) : Triac or ELV at 120V : 90 CRI : 3000K





MATERIAL Aluminum, Glass

RATINGS

cETLus Dry Location CA Title 24



## ADDITIONAL

SLOPE: RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order\_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments