
Quantity:





PRODUCT DESCRIPTION

This classic cylinder design has been made ultra-thin intending its use in applications requiring ADA compliance. The sconce casts generous lighting both upwards and downwards using dedicated, high-powered LED. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications. Available in Matte Black, Architectural Bronze and White outdoor powder coat finishes. For Dark Sky applications, make use of the optional Dark Sky Cap available.



*height from center of outlet to the top of the fixture

DIMENSION BACK PLATE HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP

LIGHTING_DIRECTION

MEASUREMENTS

: 2.5" W x 7.5" H x 3.25" Ext : 4.5" W x 4.5" H x 3.75" HCO : 2 lb

: 120-277V : 1,400 Rated (1,190 Del.) : 7W LED DC Integrated , 14W Total : (Integrated) : Triac : 90 CRI : 3000K : Up & Down

FINISHES OPTION



MATERIAL Aluminum, Glass

RATINGS cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Up RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments